The colortbl package*

David Carlisle

1998/05/06

Abstract

This package implements a flexibable mechanism for giving colured 'panels' behind specified columns in a table. This package requires the array and color packages.

1 Introduction

This package is for colouring tables (i.e., giving coloured panels behind column entries). In that it has many similarities with Timothy Van Zandt's colortab package. The internal implementation is quite different though, also colortab works with the table constructs of other formats besides LaTeX. This package requires LaTeX (and its color and array packages).

First, a standard tabular, for comparison.

```
\begin{tabular}{|l|c|}
 one&two\\
 three&four
 \end{tabular}
```

one	two
three	four

2 The `\columncolor` command

The examples below demonstrate various possibilities of the `\columncolor` command introduced by this package. The vertical rules specified by `|` are kept in all the examples, to make the column positioning clearer, although possibly you would not want coloured panels *and* vertical rules in practice.

The package supplies a `\columncolor` command, that should (only) be used in the argument of a `>` column specifier, to add a coloured panel behind the specified column. It can be used in the main 'preamble' argument of array or tabular, and also in `\multicolumn` specifiers.

The basic format is:

`\columncolor[`⟨*color model*⟩`]{`⟨*colour*⟩`} [`⟨*left overhang*⟩`][`⟨*right overhang*⟩`]`

The first argument (or first two if the optional argument is used) are standard color package arguments, as used by `\color`.

The last two arguments control how far the panel overlaps past the widest entry in the column. If the *right overhang* argument is omitted then it defaults to *left overhang*. If they are both omitted they default to `\tabcolsep` (in tabular) or `\arraycolsep` (in array).

If the overhangs are both set to `0pt` then the effect is:

*This file has version number v0.1h, last revised 1998/05/06.

```
|>{\columncolor[gray]{.8}[0pt]}l|
>{\color{white}%
  \columncolor[gray]{.2}[0pt]}l|
```

one	two
three	four

The default overhang of `\tabcolsep` produces:

```
|>{\columncolor[gray]{.8}}l|
>{\color{white}%
  \columncolor[gray]{.2}}l|
```

one	two
three	four

You might want something between these two extremes. A value of `.5\tabcolsep` produces the following effect

```
|>{\columncolor[gray]{.8}[.5\tabcolsep]}l|
 >{\color{white}%
   \columncolor[gray]{.2}[.5\tabcolsep]}l|
```

one	two
three	four

This package should work with most other packages that are compatible with the array package syntax. In particular it works with longtable and dcolumn as the following example shows.

Before starting give a little space: `\setlength\minrowclearance{2pt}`

A long table example

First two columns p-type		Third column D-type (dcolumn)
P-column	and another one	12·34
Total	(wrong)	100·6
Some long text in the first column	bbb	1·2
aaa	and some long text in the second column	1·345
Total	(wrong)	100·6
aaa	bbb	1·345
Note that the coloured rules in all columns stretch to accomodate large entries in one column.	bbb	1·345
aaa	bbb	100

Continued. . .



This example shows rather poor taste but is quite colourful! Inspect the source file, `colortbl.dtx`, to see the full code for the example, but it uses the following column types.

```
\newcolumntype{A}{%
   >{\color{white}\columncolor{red}[.5\tabcolsep]%
      \raggedright}%
   p{2cm}}
\newcolumntype{B}{%
   >{\columncolor{blue}[.5\tabcolsep]%
     \color{yellow}\raggedright}
   p{3cm}}
\newcolumntype{C}{%
    >{\columncolor{yellow}[.5\tabcolsep]}%
      D{.}{\cdot}{3.3}}
\newcolumntype{E}{%
   >{\large\bfseries
     \columncolor{cyan}[.5\tabcolsep]}c}
\newcolumntype{F}{%
    >{\color{white}
      \columncolor{magenta}[.5\tabcolsep]}c}
\newcolumntype{G}{%
    >{\columncolor[gray]{0.8}[.5\tabcolsep][\tabcolsep]}l}
\newcolumntype{H}{>{\columncolor[gray]{0.8}}l}
\newcolumntype{I}{%
    >{\columncolor[gray]{0.8}[\tabcolsep][.5\tabcolsep]}%
                  D{.}{\cdot}{3.3}}
```

3 Using the 'overhang' arguments for tabular*

The above is all very well for tabular, but what about tabular*?

Here the problem is rather harder. Although TEX's `\leader` mechanism which is used by this package to insert the 'stretchy' coloured panels is rather like *glue*, the `\tabskip` glue that is inserted between columns of tabular* (and longtable for that matter) has to be 'real glue' and not 'leaders'.

Within limits the overhang options may be used here. Consider the first table example above. If we use tabular* set to 3 cm with a preamble setting of

```
\begin{tabular*}{3cm}{%
@{\extracolsep{\fill}}
>{\columncolor[gray]{.8}[0pt][20mm]}l
>{\columncolor[gray]{.8}[5mm][0pt]}l
@{}}
```

one	**two**
three	**four**

Changing the specified width to 4 cm works, but don't push your luck to 5 cm...

one	**two**
three	**four**

one	**two**
three	**four**

4 The `\rowcolor` command

As demonstrated above, one may change the colour of specified rows of a table by the use of `\multicolumn` commands in each entry of the row. However if your table is to be marked principally by *rows*, you may find this rather inconvenient. For this reason a new mechanism, `\rowcolor`, has been introduced[1].

`\rowcolor` takes the same argument forms as `\columncolor`. It must be used at the *start* of a row. If the optional overhang arguments are not used the overhangs will default to the overhangs specified in any `\columncolor` comands for that column, or `\tabcolsep` (`\arraycolsep` in array).

If a table entry is in the scope of a `\columncolor` specified in the table preamble, and also a `\rowcolor` at the start of the current row, the colour specified by `\rowcolor` will take effect. A `\multicolumn` command may contain `>{\rowcolor...` which will override the default colours for both the current row and column.

```
\begin{tabular}{|l|c|}
 \rowcolor[gray]{.9}
 one&two\\
 \rowcolor[gray]{.5}
 three&four
 \end{tabular}
```

one	**two**
three	**four**

5 Colouring rules.

So you want coloured rules as well?

One could do vertical rules without any special commands, just use something like `!{\color{green}\vline}` where you'd normally use `|`. The space between `||` will normally be left white. If you want to colour that as well, either increase the overhang of the previous column (to `\tabcolsep` + `\arrayrulewidth`

[1] At some cost to the internal complexity of this package

+ \doublerulesep) Or remove the inter rule glue, and replace by a coloured rule of the required thickness. So

```
!{\color{green}\vline}
@{\color{yellow}\vrule width \doublerulesep}
!{\color{green}\vline}
```

Should give the same spacing as || but more colour.

However colouring \hline and \cline is a bit more tricky, so extra commands are provided (which then apply to vertical rules as well).

6 \arrayrulecolor

\arrayrulecolor takes the same arguments as \color, and is a global declaration which affects all following horizontal and vertical rules in tables. It may be given outside any table, or at the start of a row, or in a > specification in a table preamble. You should note however that if given mid-table it only affects rules that are specified after this point, any vertical rules specified in the preamble will keep their original colours.

7 \doublerulesepcolor

Having coloured your rules, you'll probably want something other than white to go in the gaps made by || or \hline\hline. \doublerulesepcolor works just the same way as \arrayrulecolor. The main thing to note that if this command is used, then longtable will not 'discard' the space between \hline\hline at a page break. (TEX has a built-in ability to discard space, but the coloured 'space' which is used once \doublerulesep is in effect is really a third rule of a different colour to the two outer rules, and rules are rather harder to discard.)

```
\setlength\arrayrulewidth{2pt}\arrayrulecolor{blue}
\setlength\doublerulesep{2pt}\doublerulesepcolor{yellow}
 \begin{tabular}{||l||c||}
  \hline\hline
  one&two\\
  three&four\\
  \hline\hline
 \end{tabular}
```

one	two
three	four

8 More fun with \hhline

The above commands work with \hhline from the hhline package, however if hhline is loaded in addition to this package, a new possibility is added. You may use >{...} to add declarations that apply to the following - or = column rule. In particular you may give \arrayrulecolor and \doublerulesepcolor declarations in this argument.

Most manuals of style warn against over use of rules in tables. I hate to think what they would make of the following rainbow example:




```
\newcommand\rainbowline[1]{%
\hhline{%
  >{\arrayrulecolor    {red}\doublerulesepcolor[rgb]{.3,.3,1}}%
  |#1:=%
  >{\arrayrulecolor{orange}\doublerulesepcolor[rgb]{.4,.4,1}}%
  =%
  >{\arrayrulecolor{yellow}\doublerulesepcolor[rgb]{.5,.5,1}}%
  =%
  >{\arrayrulecolor {green}\doublerulesepcolor[rgb]{.6,.6,1}}%
  =%
  >{\arrayrulecolor  {blue}\doublerulesepcolor[rgb]{.7,.7,1}}%
  =%
  >{\arrayrulecolor{indigo}\doublerulesepcolor[rgb]{.8,.8,1}}%
  =%
  >{\arrayrulecolor{violet}\doublerulesepcolor[rgb]{.9,.9,1}}%
  =:#1|%
  }}
\arrayrulecolor{red}
\doublerulesepcolor[rgb]{.3,.3,1}%
\begin{tabular}{||*7{>{\columncolor[gray]{.9}}c}||}
\rainbowline{t}%
\arrayrulecolor{violet}\doublerulesepcolor[rgb]{.9,.9,1}
Richard&of&York&gave&battle&in&
\multicolumn{1}{>{\columncolor[gray]{.9}}c||}{vain}\\
\rainbowline{}%
1&2&3&4&5&6&
\multicolumn{1}{>{\columncolor[gray]{.9}}c||}{7}\\
\rainbowline{b}%
\end{tabular}
```

9 Less fun with `\cline`

Lines produced by `\cline` are coloured if you use `\arrayrulecolor` but you may not notice as they are covered up by any colour pannels in the following row. This is a 'feature' of `\cline`. If using this package you would probably better using the `-` rule type in a `\hhline` argument, rather than `\cline`.

10 The `\minrowclearance` command

As this package has to box and measure every entry to figure out how wide to make the rules, I thought I may as well add the following feature. 'Large' entries in tables may touch a preceding `\hline` or the top of a colour panel defined by this style. It is best to increase `\extrarowsep` or `\arraystretch` sufficiently to

ensure this doesn't happen, as that will keep the line spacing in the table regular. Sometimes however, you just want to LaTeX to insert a bit of extra space above a large entry. You can set the length `\minrowclearance` to a small value. (The height of a capital letter plus this value should not be greater than the normal height of table rows, else a very uneven table spacing will result.)

Donald Arseneau's tabls packages provides a similar `\tablinesep`. I was going to give this the same name for compatibility with tabls, but that is implemented quite differently and probably has different behaviour. So I'll keep a new name for now.

11 The Code

```
⟨*package⟩
```

Nasty hacky way used by all the graphics packages to include debugging code.

```
\edef\@tempa{%
  \noexpand\AtEndOfPackage{%
    \catcode`\noexpand\^^A\the\catcode`\^^A\relax}}
\@tempa
\catcode`\^^A=\catcode`\%
\DeclareOption{debugshow}{\catcode`\^^A=9 }
```

All the other options are handled by the color package.

```
\DeclareOption*{\PassOptionsToPackage\CurrentOption{color}}
\ProcessOptions
```

I need these so load them now. Actually Mark Wooding's mdwtab package could probably work instead of array, but currently I assume array package internals so...

```
\RequirePackage{array,color}
```

`\@classz` `\@classz` is the main function in the array package handling of primitive column types: It inserts the code for each of the column specifiers, '`clrpmb`'. The other classes deal with the other preamble tokens such as '`@` 'or '`>`'.

```
\def\@classz{\@classx
   \@tempcnta \count@
   \prepnext@tok
```

At this point the colour specification for the background panel will be in the code for the '`>`' specification of this column. This is saved in `\toks\@temptokena` but array will insert it too late (well it would work for `c`, but not for `p`) so fish the colour stuff out of that token register by hand, and then insert it around the entry.

Of course this is a terrible hack. What is really needed is a new column type that inserts stuff in the right place (rather like `!` but without the spacing that that does). The `\newcolumntype` command of array only adds 'second class' column types. The re-implementations of `\newcolumntype` in my blkarray or Mark Wooding's mdwtab allow new 'first class' column types to be declared, but stick with array for now. This means we have to lift the stuff out of the register before the register gets emptied in the wrong place.

```
\expandafter\CT@extract\the\toks\@tempcnta\columncolor!\@nil
```

Save the entry into a box (using a double group for colour safety as usual).

```
   \@addtopreamble{%
    \setbox\z@\hbox\bgroup\bgroup
      \ifcase \@chnum
```

`c` code: This used to use twice as much glue as `l` and `r` (1fil on each side). Now modify it to use 1fill total. Also increase the order from 1fil to 1fill to dissuade people from putting stretch glue in table entries.

```
      \hskip\stretch{.5}\kern\z@
      \d@llarbegin
      \insert@column
      \d@llarend\hskip\stretch{.5}\or
```

`l` and `r` as before, but using fill glue.

```
      \d@llarbegin \insert@column \d@llarend \hfill \or
      \hfill\kern\z@ \d@llarbegin \insert@column \d@llarend \or
```

`m`, `p` and `b` as before.

```
   $\vcenter
   \@startpbox{\@nextchar}\insert@column \@endpbox $\or
   \vtop \@startpbox{\@nextchar}\insert@column \@endpbox \or
   \vbox \@startpbox{\@nextchar}\insert@column \@endpbox
  \fi
```

Close the box register assignment.

```
 \egroup\egroup
```

The main new stuff.

```
\begingroup
```

Initalise colour command and overhands.

```
  \CT@setup
```

Run any code resulting from `\columncolor` commands.

```
  \CT@column@color
```

Run code from `\rowcolor` (so this takes precedence over `\columncolor`).

```
  \CT@row@color
```

This is `\relax` unless one of the two previous commands has requested a colour, in which case it will be `\CT@@do@color` which will insert `\leaders` of appropriate colour.

```
  \CT@do@color
\endgroup
```

Nothing to do with colour this bit, since we are boxing and measuring the entry anyway may as well check the height, so that large entries don't bump into horizontal rules (or the top of the colour panels).

```
        \@tempdima\ht\z@
        \advance\@tempdima\minrowclearance
        \vrule\@height\@tempdima\@width\z@
```

It would be safer to leave this boxed, but unboxing allows some flexibilty. However the total glue stretch should either be finite or fil (which will be ignored). There may be fill glue (which will not be ignored) but it should *total 0fill*. If this box contributes fill glue, then the leaders will not reach the full width of the entry. In the case of `\multicolumn` entries it is actually possible for this box to contribute *shrink* glue, in which case the coloured panel for that entry will be too wide. Tough luck.

```
        \unhbox\z@}%
  \prepnext@tok}
```

`\CT@setup` Initialise the overhang lengths and the colour command.

```
\def\CT@setup{%
  \@tempdimb\col@sep
  \@tempdimc\col@sep
  \def\CT@color{%
    \global\let\CT@do@color\CT@@do@color
    \color}}
```

`\CT@@do@color` The main point of the package: Add the colour panels.

Add a leader of the specified colour, with natural width the width of the entry plus the specified overhangs and 1fill stretch. Surround by negative kerns so total natural width is not affected by overhang.

```
\def\CT@@do@color{%
  \global\let\CT@do@color\relax
        \@tempdima\wd\z@
        \advance\@tempdima\@tempdimb
        \advance\@tempdima\@tempdimc
        \kern-\@tempdimb
        \leaders\vrule
```

For quick debugging with xdvi (which can't do colours). Limit the size of the rule, so I can see the text as well.

```
^^A                     \@height\p@\@depth\p@
                \hskip\@tempdima\@plus  1fill
        \kern-\@tempdimc
```

Now glue to exactly compensate for the leaders.

```
        \hskip-\wd\z@ \@plus -1fill }
```

`\CT@extract` Now the code to extract the `\columncolor` commands.

```
\def\CT@extract#1\columncolor#2#3\@nil{%
  \if!#2%
```

`!` is a fake token inserted at the end.

```
    \let\CT@column@color\@empty
  \else
```

If there was an optional argument

```
    \if[#2%
      \CT@extractb{#1}#3\@nil
    \else
```

No optional argument

```
      \def\CT@column@color{%
        \CT@color{#2}}%
      \CT@extractd{#1}#3\@nil
    \fi
  \fi}
```

`\CT@extractb` Define `\CT@column@color` to add the right colour, and save the overhang lengths. Finally reconstitute the saved '`>`' tokens, without the colour specification. First grab the colour spec, with optional arg.

```
\def\CT@extractb#1#2]#3{%
  \def\CT@column@color{%
    \CT@color[#2]{#3}}%
  \CT@extractd{#1}}%
```

\CT@extractd Now look for left-overhang (default to \col@sep).

```
\def\CT@extractd#1{\@testopt{\CT@extracte{#1}}\col@sep}
```

\CT@extracte Same for right-overhang (default to left-overhang).

```
\def\CT@extracte#1[#2]{\@testopt{\CT@extractf{#1}[#2]}{#2}}
```

\CT@extractf Add the overhang info to \CT@do@color, for excuting later.

```
\def\CT@extractf#1[#2][#3]#4\columncolor#5\@nil{%
  \@tempdimb#2\relax
  \@tempdimc#3\relax
  \edef\CT@column@color{%
    \CT@column@color
    \@tempdimb\the\@tempdimb\@tempdimc\the\@tempdimc\relax}%
  \toks\@tempcnta{#1#4}}%
```

\CT@everycr Steal \everypar to initialise row colours

```
\let\CT@everycr\everycr
\newtoks\everycr
\CT@everycr{\noalign{\global\let\CT@row@color\relax}\the\everycr}
```

\CT@start

```
\def\CT@start{%
  \let\CT@arc@save\CT@arc@
  \let\CT@drsc@save\CT@drsc@
  \let\CT@row@color@save\CT@row@color}
```

\CT@end

```
\def\CT@end{%
  \global\let\CT@arc@\CT@arc@save
  \global\let\CT@drsc@\CT@drsc@save
  \global\let\CT@row@color\CT@row@color@save}
```

\shortstack \shortstack

```
\gdef\@ishortstack#1{%
  \CT@start\ialign{\mb@l {##}\unskip\mb@r\cr #1\crcr}\CT@end\egroup}
```

\@tabarray array and tabular (delayed for delarray)

```
\AtBeginDocument{%
  \expandafter\def\expandafter\@tabarray\expandafter{%
    \expandafter\CT@start\@tabarray}}
```

\endarray

```
\def\endarray{\crcr \egroup \egroup \gdef\@preamble{}\CT@end}
```

\multicolumn \multicolumn

```
\def\multicolumn#1#2#3{%
   \multispan{#1}\begingroup
   \def\@addamp{\if@firstamp \@firstampfalse \else
                \@preamerr 5\fi}%
   \@mkpream{#2}\@addtopreamble\@empty
   \endgroup
   \def\@sharp{#3}%
   \let\CT@row@color\relax
```

```
    \let\CT@column@color\relax
    \let\CT@do@color\relax
    \@arstrut \@preamble
    \null
    \ignorespaces}
```

`\@classvi` Coloured rules and rule separations.

```
\def\@classvi{\ifcase \@lastchclass
      \@acol \or
      \ifx\CT@drsc@\relax
        \@addtopreamble{\hskip\doublerulesep}%
      \else
        \@addtopreamble{{\CT@drsc@\vrule\@width\doublerulesep}}%
      \fi\or
      \@acol \or
      \@classvii
      \fi}
```

`\doublerulesepcolor`

```
\def\doublerulesepcolor#1#{\CT@drs{#1}}
```

`\CT@drs`

```
\def\CT@drs#1#2{%
 \ifdim\baselineskip=\z@\noalign\fi
  {\gdef\CT@drsc@{\color#1{#2}}}}
```

`\CT@drsc@`

```
\let\CT@drsc@\relax
```

`\arrayrulecolor`

```
\def\arrayrulecolor#1#{\CT@arc{#1}}
```

`\CT@arc`

```
\def\CT@arc#1#2{%
  \ifdim\baselineskip=\z@\noalign\fi
  {\gdef\CT@arc@{\color#1{#2}}}}
```

`\CT@arc@`

```
\let\CT@arc@\relax
```

hline

`\@arrayrule`

```
\def\@arrayrule{\@addtopreamble {{\CT@arc@\vline}}}
```

`\hline`

```
\def\hline{%
  \noalign{\ifnum0=`}\fi
               \let\hskip\vskip
                \let\vrule\hrule
                \let\@width\@height
  {\CT@arc@\vline}%
  \futurelet
   \reserved@a\@xhline}
```

\@xhline

```
\def\@xhline{\ifx\reserved@a\hline
               {\ifx\CT@drsc@\relax
                  \vskip
               \else
                  \CT@drsc@\hrule\@height
               \fi
               \doublerulesep}%
             \fi
      \ifnum0=‘{\fi}}
```

\cline `\cline` doesn't really work, as it comes behind the coloured panels, but at least make it the right colour (the bits you can see, anyway).

```
\def\@cline#1-#2\@nil{%
  \omit
  \@multicnt#1%
  \advance\@multispan\m@ne
  \ifnum\@multicnt=\@ne\@firstofone{&\omit}\fi
  \@multicnt#2%
  \advance\@multicnt-#1%
  \advance\@multispan\@ne
  {\CT@arc@\leaders\hrule\@height\arrayrulewidth\hfill}%
  \cr
  \noalign{\vskip-\arrayrulewidth}}
```

\minrowclearance The row height fudge length.

```
\newlength\minrowclearance
\minrowclearance=0pt
```

\@mkpream While expanding the preamble array passes tokens through an `\edef`. It doesn't use `\protection` as it thinks it has full control at that point. As the redefinition above adds `\color`, I need to add that to the list of commands made safe.

```
\expandafter\def\expandafter\@mkpream\expandafter#\expandafter1%
  \expandafter{%
    \expandafter\let\expandafter\CT@setup\expandafter\relax
    \expandafter\let\expandafter\CT@color\expandafter\relax
    \expandafter\let\expandafter\CT@do@color\expandafter\relax
    \expandafter\let\expandafter\color\expandafter\relax
    \expandafter\let\expandafter\CT@column@color\expandafter\relax
    \expandafter\let\expandafter\CT@row@color\expandafter\relax
    \@mkpream{#1}}
```

\CT@do@color For similar reasons, need to make this non-expandable

```
\let\CT@do@color\relax
```

\rowcolor

```
\def\rowcolor{%
  \noalign{\ifnum0=‘}\fi
  \global\let\CT@do@color\CT@@do@color
  \@ifnextchar[\CT@rowa\CT@rowb}
```

\CT@rowa

```
\def\CT@rowa[#1]#2{%
```

```
  \gdef\CT@row@color{\CT@color[#1]{#2}}%
  \CT@rowc}
```

`\CT@rowb`

```
\def\CT@rowb#1{%
  \gdef\CT@row@color{\CT@color{#1}}%
  \CT@rowc}
```

`\CT@rowc`

```
\def\CT@rowc{%
  \@ifnextchar[\CT@rowd{\ifnum`{=0\fi}}}
```

`\CT@rowd`

```
\def\CT@rowd[#1]{\@testopt{\CT@rowe[#1]}{#1}}
```

`\CT@rowe`

```
\def\CT@rowe[#1][#2]{%
  \@tempdimb#1%
  \@tempdimc#2%
  \xdef\CT@row@color{%
    \expandafter\noexpand\CT@row@color
    \@tempdimb\the\@tempdimb
    \@tempdimc\the\@tempdimc
    \relax}%
  \ifnum0=`{\fi}}
```

`\DC@endright` dcolumn support. the `D` column sometimes internally converts a `c` column to an `r` one by squashing the supplied glue. This is bad news for this package, so redefine it to add negative glue to one side and positive to the other to keep the total added zero.

```
\AtBeginDocument{%
  \def\@tempa{$\hfil\egroup\box\z@\box\tw@}%
  \ifx\@tempa\DC@endright
```

New version of dcolumn, only want to fudge it in the `D{.}{.}{3}` case, not the new `D{.}{.}{3.3}` possibility. `\hfill` has already been inserted, so need to remove 1fill's worth of stretch.

```
    \def\DC@endright{%
      $\hfil\egroup
    \ifx\DC@rl\bgroup
      \hskip\stretch{-.5}\box\z@\box\tw@\hskip\stretch{-.5}%
    \else
      \box\z@\box\tw@
    \fi}%
  \else
    \def\@tempa{$\hfil\egroup\hfill\box\z@\box\tw@}%
    \ifx\@tempa\DC@endright
```

Old dcolumn code.

```
      \def\DC@endright{%
        $\hfil\egroup%
        \hskip\stretch{.5}\box\z@\box\tw@\hskip\stretch{-.5}}%
    \fi
  \fi}
```

hhline support (almost the whole package, repeated, sigh).

```
\AtBeginDocument{%
  \ifx\hhline\@undefined\else
\def\HH@box#1#2{\vbox{{%
  {\CT@drsc@\dimen@\tw@\arrayrulewidth
   \advance\dimen@\doublerulesep
   \hrule \@height\dimen@
   \vskip-\dimen@}%
  \CT@arc@
  \hrule \@height \arrayrulewidth \@width #1
  \vskip\doublerulesep
  \hrule \@height \arrayrulewidth \@width #2}}}
\def\HH@loop{%
  \ifx\@tempb`\def\next##1{\the\toks@\cr}\else\let\next\HH@let
  \ifx\@tempb|\if@tempswa
          \ifx\CT@drsc@\relax
           \HH@add{\hskip\doublerulesep}%
          \else
           \HH@add{{\CT@drsc@\vrule\@width\doublerulesep}}%
           \fi
          \fi\@tempswatrue
          \HH@add{{\CT@arc@\vline}}\else
  \ifx\@tempb:\if@tempswa
          \ifx\CT@drsc@\relax
           \HH@add{\hskip\doublerulesep}%
          \else
           \HH@add{{\CT@drsc@\vrule\@width\doublerulesep}}%
           \fi
              \fi\@tempswatrue
      \HH@add{\@tempc\HH@box\arrayrulewidth\arrayrulewidth\@tempc}\else
  \ifx\@tempb##\if@tempswa\HH@add{\hskip\doublerulesep}\fi\@tempswatrue
         \HH@add{{\CT@arc@\vline\copy\@ne\@tempc\vline}}\else
  \ifx\@tempb~\@tempswafalse
           \if@firstamp\@firstampfalse\else\HH@add{&\omit}\fi
              \ifx\CT@drsc@\relax
                \HH@add{\hfil}\else
                 \HH@add{{%
\CT@drsc@\leaders\hrule\@height\doublerulesep\hfil}}%
               \fi
                 \else
  \ifx\@tempb-\@tempswafalse
           \if@firstamp\@firstampfalse\else\HH@add{&\omit}\fi
              \HH@add{{%
                \CT@arc@\leaders\hrule\@height\arrayrulewidth\hfil}}%
                           \else
  \ifx\@tempb=\@tempswafalse
       \if@firstamp\@firstampfalse\else\HH@add{&\omit}\fi
       \HH@add
          {\rlap{\copy\@ne}\leaders\copy\@ne\hfil\llap{\copy\@ne}}\else
```

Stop the backspacing for `t` and `b`, it messes up the underlying colour.

```
  \ifx\@tempb t\HH@add{\HH@box\doublerulesep\z@}\@tempswafalse\else
  \ifx\@tempb b\HH@add{\HH@box\z@\doublerulesep}\@tempswafalse\else
  \ifx\@tempb>\def\next##1##2{%
```

```
    \HH@add{%
     {\baselineskip\p@\relax
      ##2%
     \global\setbox\@ne\HH@box\doublerulesep\doublerulesep}}%
      \HH@let!}\else
  \PackageWarning{hhline}%
      {\meaning\@tempb\space ignored in \noexpand\hhline argument%
       \MessageBreak}%
  \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi
  \next}
\fi}
```

longtable support.

```
\AtBeginDocument{
  \ifx\longtable\@undefined\else
    \def\LT@@hline{%
      \ifx\LT@next\hline
        \global\let\LT@next\@gobble
        \ifx\CT@drsc@\relax
          \gdef\CT@LT@sep{%
            \noalign{\penalty-\@medpenalty\vskip\doublerulesep}}%
        \else
          \gdef\CT@LT@sep{%
            \multispan\LT@cols{%
              \CT@drsc@\leaders\hrule\@height\doublerulesep\hfill}\cr}%
        \fi
      \else
        \global\let\LT@next\empty
        \gdef\CT@LT@sep{%
          \noalign{\penalty-\@lowpenalty\vskip-\arrayrulewidth}}%
      \fi
      \ifnum0=`{\fi}%
      \multispan\LT@cols
       {\CT@arc@\leaders\hrule\@height\arrayrulewidth\hfill}\cr
      \CT@LT@sep
      \multispan\LT@cols
       {\CT@arc@\leaders\hrule\@height\arrayrulewidth\hfill}\cr
      \noalign{\penalty\@M}%
      \LT@next}
    \fi}
```

⟨/package⟩