Refinement Calculus

(and Martin-Löf type theory)

Peter Hancock

peter@premise.demon.co.uk

http://www.dcs.ed.ac.uk/~pgh

March 2002

Summary

Some (unexpected) connections between the refinement calculus (Back, Morris, Morgan, von-Wright, ...) and Petersson-Synek trees in Martin-Löf type theory.

Suggests a normal form for specifications of certain kinds of interactive program (angelic "user-side" programs and demonic "system-side" programs), expressible with dependent types. A proof that a specification is satisfiable is in principle executable as a program of the appropriate kind.

Many questions raised. I'd like your opinion.

Collaborators
Anton Setzer (Swansea)
– input-output monads and coalgebras
Pierre Hyvernat (Lyons/Chalmers)
– implementation
My own interest
– specifications using dependent types.

How to deal with interaction (action/reaction) in type theory?

What kind of proof is it that

- runs an internet server to book plane-flights and hotel rooms?
- prevents the brakes on a bus from locking in a skid?
- flies a cruise missile?

What proposition does it prove, and how is this connected with a specification of the desired behaviour?

Context: strength of a programming logic

batch $Input \xrightarrow{f} Output$

Input/output is available *in its entirity* when execution starts/terminates.

Strength: the set of batch programs that can be proved to terminate.
(Termination strength, provably total recursive functions)

transaction Input is consumed and output is produced *piece by piece*. Eventual termination.

Strength: the set of transaction programs that can be proved to terminate (*i.e.* with output available *in its entirity*) given a sufficiently long sequence of inputs.
(Continuity, well-foundedness, ...)

A model of imperative interfaces

Two levels of choice:

angel, client	*demon, server*
stimulus,	response
command,	response
action,	reaction
move,	counter-move
call,	return
C,	R

S : set, (*States*)

$C(x)$: set $(x \in S)$, (*Angel*)

$R(x, y)$: set $(x \in S, y \in C(x))$, (*Demon*)

$n(x, y, z) : S\,(x \in S, y \in C(x), z \in R(x, y))$ (*next*)

For each $s \in S$ a family of families of outcomes:

$$\{\,\{\,n(s, c, r) \mid r \in R(s, c)\,\} \mid c \in C(s)\,\}$$

Interaction structure

$$\Phi : S \to \mathbb{F}(\mathbb{F}(S'))$$

$s \in \mathbf{S}$	a state (position)
$c \in \mathbf{C}(s)$	an input (action) in state $s \in S$
$r \in \mathbf{R}(s,c)$	an output (reaction)
	in response to $c \in C(s)$
$s[c\,/\,r] : S'$	the new state after interaction c/r.
$= \mathbf{n}(s,c,r)$	notation

Interaction system

$$(S : \mathsf{set}, \Phi : S \to \mathbb{F}(\mathbb{F}(S)), s_0 \in S)$$

Notions of powerset

subset S	*notation*
$\mathbb{P}(S) = \mathsf{set}^S$	$P = \{\, s \in S \mid P(s) \,\}$
$\mathbb{F}(S) = (\exists T : \mathsf{set}) S^T$	$\langle T, s \rangle = \{\, s(t) \mid t \in T \,\}$

Predicates to families:
'Σ-types' and (first) projection.

$$P \mapsto \{\, \pi_0(z) \mid z \in (\exists\, s \in S) P(s) \,\}$$

Families to predicates: singleton predicates*
$\{\, s \,\} = \{\, s' \in S \mid s' =_S s \,\}$.

$$\{\, s(t) \mid t \in T \,\} \mapsto \{\, s' \in S \mid s' =_S s(t) \,\}$$

(*: Singleton predicates are evil.)

The programmer's firmament

Function
$A \to B$

Relation
$A \to \mathbb{P}(B)$

Transition Structure
$A \to \mathbb{F}(B)$

Predicate Transformer
$A \to \mathbb{P}(\mathbb{P}(B))$
$\cong \mathbb{P}(B) \to \mathbb{P}(A)$
(flip)

Interaction Structure
$A \to \mathbb{F}(\mathbb{F}(B))$

Interaction structures as predicate transformers

Given $\Phi : S \to \mathbb{F}(\mathbb{F}(S'))$,
define $\Phi^\circ : \mathbb{P}(S') \to \mathbb{P}(S)$.

$$\Phi^\circ(X) = \{\, s \in S \mid (\exists\, c \in C_\Phi(s)) \; (\forall\, r \in R_\Phi(s,c)) \; X(n_\Phi(s,c,r)) \,\}$$

"DNF" (Disjunctive Normal Form).

Aside : conjunctive normal form doesn't work.

The refinement calculus

- predicate transformers (business end):

$$\begin{array}{rcl} \Phi, \Psi & ::= & \bullet \quad \text{abort}, \quad \text{magic}, \\ & & \quad\ \Phi \sqcup \Psi, \quad \Phi \sqcap \Psi, \\ & & \quad\ \sqcup_i \Phi_i, \quad \sqcap_i \Phi_i, \\ & & \quad\ \langle \phi \rangle, \quad\ [\phi] \\ & & \bullet \quad \text{skip}, \quad (\Phi \ ; \Psi) \end{array}$$

$$\Phi \sqsubseteq \Psi \ = \ \forall X. \, \Phi(X) \subseteq \Psi(X)$$

- relations: $R \ ::= \ \ldots \qquad \phi \ ::= \ \ldots$

- predicates: $P, Q \ ::= \ \ldots$

- state transformers: $f, g \ ::= \ \ldots$

- ergonomics.

Semantic hijack
e.g. sequential composition

$$
\begin{aligned}
&C_{\Phi;\Psi}(s) \\
&\quad = (\exists\, c \in C_\Phi(s))(\forall\, r \in R_\Phi(s,c)) C_\Psi(n_\Phi(s,c,r)) \\
&\quad = \Phi^\circ(C_\Psi, s) \\
&R_{\Phi;\Psi}(s, \langle c, f\rangle) \\
&\qquad = \ (\exists\, r \in R_\Phi(s,c)) R_\Psi(n_\Phi(s,c,r), f(r)) \\
&n_{\Phi;\Psi}(s, \langle c, f\rangle, \langle r, r'\rangle) \\
&\qquad = n_\Psi(n_\Phi(s,c,r), f(r), r')
\end{aligned}
$$

Have to check $(\Phi;\Psi)^\circ = \Phi^\circ \cdot \Psi^\circ$.

Proof: axiom of choice, amalgamation of same-sex quantifiers.

Two forms of recursion

$$\begin{aligned} \Phi^* &= \mu\Psi.\ \mathsf{skip} \sqcup (\Phi\ ;\ \Psi) \\ \Phi^\infty &= \nu\Psi.\ \mathsf{skip} \sqcap (\Phi\ ;\ \Psi) \end{aligned}$$

Φ^*: inductively defined (Petersson and Synek). We have to terminate eventually, but we can choose when. Formally a closure operator.

Φ^∞: coinductively defined. They can choose to terminate at any point, or not at all. Formally an interior operator.

$Y = \Phi^\infty(X)$ is the weakest invariant of Φ (i.e. post fixed point, satisfying $Y \subseteq \Phi(Y)$) that implies X.

$Y = \Phi^*(X)$ is also an invariant (Lambek). It is the strongest invariant of Φ that is implied by X holding eventually.

$\Phi^\sim = \Phi$ with the angel and the demon swapped.

What theorem is proved by a c/r-program?

(First approximation.)

a client (terminating) $A \subseteq \Phi^*(B)$

Requires A initially, guarantees B finally (provided there is a 'finally').

'overlaps'

$\downarrow$

a server (perpetual) $A \rangle\!(\Psi^\infty(B)$

Guarantees A initially, and B perpetually.

where $\Psi = \Phi^\sim$. Problem: relate state in B to state in A.

More grit

Given

$$A : \mathbb{P}(S)$$
$$B : \forall s \in S.\, A(s) \to \mathbb{P}(S)$$

initial condition, termination/invariant condition

$$(\forall\, s \in S, p \in A(s))\, \Phi^*(B(s,p), s)$$
$$(\exists\, s \in S, p \in A(s))\, \Psi^\infty(B(s,p), s)$$

Inconclusion

I freely admit I don't (continuously) find these suggestions very convincing.

Some directions:

- Case studies.
- Thorough study of refinement calculus. (Different sub-species of predicate transformer:
  conjunctive, continuous, . . . commuting with intersections/unions of various kinds)
- Relate to work linear-time temporal logic. (*eg.* Lamport's TLA.)
- Relate to work in formal topology. (Sambin, Mulvey *etc.*)

Work on type theory: coinduction
(in 'intensional' type theory).